

In the claims

Please amend the claims as follows:

1. (Previously presented) A dual lock apparatus of the type including a locking bolt moveable between a first position whereby said locking bolt extends outwardly from said apparatus and a second position whereby said locking bolt is contained within said apparatus, said apparatus including:

a slider moveable between a first position and a second position and including a first end associated with said locking bolt such that movement of the slider causes corresponding movement of the locking bolt, and a second end associated with a key lock and a motor lock whereby independent operation of the key lock and motor lock is controlled by a clutch mechanism;

said clutch mechanism including an aperture which extends through said slider and a coupling member moveable between at least a first and second position within said slider aperture;

said motor lock including a slidable member moveable between a first and second position, said slidable member including an outwardly biased locking member adapted to engage said slider aperture to thereby mechanically connect said motor lock with said slider to thereby effect movement of said slider upon movement of said slidable member;

said key lock including a rotatable cam such that, when rotated, said cam

acts against said coupling member to thereby move said coupling member from said first position to said second position to thereby mechanically the key lock with said slider to thereby effect movement of said slider.

2. (Currently amended) A The dual lock apparatus as in claim 1 wherein said the key lock disengages said motor lock.
3. (Currently amended) A The dual lock apparatus as in claim 1 wherein when said key lock has locked said locking bolt, motor lock cannot unlock said locking bolt.
4. (Currently amended) A The dual lock apparatus as in claim 1, wherein said motor lock is electrically driven.
5. (Currently amended) A The dual lock apparatus as in claim 1 wherein said key lock is a key activated locking means whilst motor lock is an electromechanical locking means.
6. (Currently amended) A The dual lock apparatus as in claim 1 wherein both the key lock and the motor lock are key activated.
7. (Currently amended) A The dual lock apparatus as in claim 1, wherein when said slider interacts with said locking bolt so as to move it into said first position

and said slider resists withdrawal of said locking bolt.

8. (Previously presented) A dual lock apparatus of the type including a locking bolt moveable between a first locked position to engage with an external restraining means and a second unlocked position, said apparatus including:

a slider adapted to interact with said locking bolt so as to move it into said first or second position, said slider including at one end an aperture extending perpendicularly to the direction of motion of said slider, said aperture adapted to house a slider abutment member;

said slider abutment member being moveable between a first position whereby a surface of said slider abutment member is flush with a surface of said slider and a second position whereby said surface of said slider abutment member is housed within said aperture;

a carriage associated with said slider, said carriage including an abutment surface, said carriage further being moveable between a first position wherein said slider is located in said slider second position, and a second position thereby urging said slider into said slider first position;

a key lock having a rotatable cam such that when rotated in a first direction it acts so as to act against said carriage abutment surface thereby urging said carriage into said carriage second position and said slider abutment member into said first position to thereby urge the slider towards its first position and thereby outwardly extend said locking bolt; and when said cam is rotated in an opposite direction it acts to urge the slider towards its second position to thereby inwardly retract said locking bolt;

and

a motor lock adapted to be activated independent of said key lock and including a moveable member associated with said slider and being moveable between a first position whereby said locking bolt is inwardly retracted and a second position whereby said locking bolt is outwardly extended; said moveable member including a rack cavity that houses an outwardly biased pin and being moveable between a first and a second position, in said first position said pin engaging with said slider aperture to thereby effectively mechanically couple said motor lock to said slider and thus the locking bolt and in said second position said pin forced into said rack cavity whereby said slider may freely move to thereby effectively decouple said motor lock from the slider, this occurring when said slider abutment member is in said member first position.

9. (Currently amended) A The dual lock apparatus as in claim 8 further comprising a biasing member and wherein when said cam discontinues urging of said carriage, said biasing member acts upon said pin to return it to said first position upon alignment of said pin and said slider aperture.

10. (Currently amended) A dual lock apparatus of the type including a locking bolt moveable between a first locked position and a second unlocked position, said locking bolt movement corresponding with longitudinal movement of a slider, said apparatus including:

a key locking means and a motor locking means adapted to operate independently of one another; said key locking means including a rotatable cam such

that when rotated said cam acts against a moveable coupling member to thereby move said coupling member from a first position to a second position in which the motor locking means becomes disengaged from said slider and further rotation of the cam urges longitudinal movement of the slider;

said motor locking means including an electric motor in geared connection to a member moveable between a first position and a second position corresponding with the respective locked and unlocked positions of the locking bolt, said member including an outwardly biased pin adapted to engage a cylinder associated with said coupling member and thereby urge said coupling member into said ~~piston~~ coupling member first position to thereby mechanically couple the motor locking means with the slider.